



**STOCKED
IN
HOUSTON,
TEXAS**

GS Series

GS-1: 582 lumens | 1.8 lbs (0.8 kg)
GS-2: 1,292 lumens | 2.6 lbs (1.2 kg)
Lengths: GS-1: 15.5" | GS-2: 26.5"

AC Input voltage: 120 VAC +/- 10%
DC Input voltage: 24 VDC
Ambient temp. range: -40°C to +65°C
Ingress protection: IP66/67

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



BL Series

BL40: 4,475 lumens | 6.4 lbs (2.9 kg)
Dimensions: 18.43" x 5.65" x 3.93"

AC Input voltage: 120-277 VAC
Ambient temp. range: -40°C to +65°C
Ingress protection: IP66

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



NL Series

NL2-H: 5,143 lumens | 12 lbs (5.3 kg)
NL4-S: 8,697 lumens | 19 lbs (8.6 kg)
Lengths: NL-2: 27.3" | NL-4: 50.8"

AC Input voltage: 120-277 VAC
Ambient temp. range: -40°C to +55°C
Ingress protection: IP66

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



MR Series

MR6: 6,283 lumens | 10.4 lbs (4.6 kg)
Dimensions: 14.5" x 11.5" x 2.5"

AC Input voltage: 120-277 VAC
Ambient temp. range: -40°C to +55°C
Ingress protection: IP66/67

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



XR Series

XR15: 12,866 lumens | 17.8 lbs (8.1 kg)
Dimensions: 18.74" x 14.88" x 3.78"

AC Input voltage: 120-277 VAC
Ambient temp. range: -50°C to +75°C
Ingress protection: IP66

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



Harsh & Hazardous Location Lights

View All Products Online





GS Series

GS Product Page



GS-1-50-W-BLK-H-120-66-A

GS SERIES; ONE FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS LOCATION; 120 VAC 60Hz; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-2-50-W-BLK-H-120-66-A

GS SERIES; TWO FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS LOCATION; 120 VAC 60Hz; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-1-50-W-BLK-H-24-66-A

GS SERIES; ONE FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS LOCATION; 22-28 VDC; IP66 INGRESS PROTECTION; ADJUSTABLE BRACKET

GS-2-50-W-BLK-H-24-66-A

GS SERIES; TWO FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS LOCATION; 22-28 VDC; IP66 INGRESS PROTECTION; ADJUSTABLE BRACKET

BL Series

BL Product Page



BL40-50-GY-HZ-AC

BL 40 SERIES; 5000K ; GREY FINISH; HAZARDOUS LOCATION; 120-277VAC

BL-YM

BL SERIES; ADJUSTABLE YOKE MOUNT

BL-WM

BL SERIES; WALL MOUNT

BL-SM

BL SERIES; SURFACE MOUNT

BL-TC

BL SERIES; TUBE CLAMP MOUNT

NL Series

NL Product Page



NL2-H-50-WC-GY-HZ-AC

NL2 SERIES; HIGH OUTPUT; 5000K ; WIDE CLEAR LENS; GREY FINISH; HAZARDOUS LOCATION; 120-277VAC

NL4-S-50-WC-GY-HZ-AC

NL4 SERIES; HIGH OUTPUT; 5000K ; WIDE CLEAR LENS; GREY FINISH; HAZARDOUS LOCATION; 120-277VAC

NL-SM

NL SERIES; SURFACE MOUNT

NL-AM-GY

NL SERIES; ANGLE ADJ. MOUNT; GREY FINISH

MR Series

MR Product Page



MR6-50-WF-GY-HZ-AC

MR 6 SERIES; 5000K ; WIDE BEAM (NO OPTICS); GREY FINISH; HAZARDOUS LOCATION; 120-277VAC

MR-PM

MR SERIES; POLE MOUNT

MR-YM

MR SERIES; ADJUSTABLE YOKE MOUNT

XR Series

XR Product Page



XR15-50-WC-GY-HZ-AC

XR 15 SERIES; 5000K ; WIDE BEAM (NO OPTICS); GREY FINISH; HAZARDOUS LOCATION; 120-277VAC

XR-SFY-GY-HZ*

XR SERIES; SLIP FITTER YOKE MOUNT; GREY FINISH; HAZARDOUS LOCATION

XR-PM

XR SERIES; POLE MOUNT

XR-YM

XR SERIES; ADJUSTABLE YOKE MOUNT

*The XR Slip Fitter Yoke Mount (SFY) is compatible with the MR