

## LIGHTING THAT IMPROVES WORKSITE SAFETY



View All Products Online



### MR Series

3,000 – 6,000 lumen fixture



IP66 / IP67 / IP68\*  
GN & HZ

4.6 kg | 10.4 lbs  
14.5" x 11.5" x 2.5"



### GS Series

582 – 5,125 lumen fixture



IP66 / IP67 / IP68\*  
GN & HZ



GS1: 0.8 kg | 1.8 lbs GS2: 1.2 kg | 2.6 lbs  
GS3: 1.8 kg | 3.9 lbs GS4: 2.4 kg | 5.3 lbs



### CANLED Series

469 – 587 lumen fixture



IP66  
GN & HZ

1.04 kg | 2.3 lbs  
Ø3.47" x 5.29"



### XR Series

8,000 – 20,000 lumen fixture



IP66 / IP68\*  
GN & HZ

8.1 kg | 17.8 lbs  
18.74" x 14.88" x 3.78"



### BL Series

2,540 – 4,475 lumen fixture



IP66 / IP68\*  
GN & HZ

2.9 kg | 6.4 lbs  
18.43" x 5.65" x 3.93"



### XCANLED Series

1,996 – 2,334 lumen fixture



IP66  
GN & HZ

4.3 kg | 9.5 lbs  
Ø7.0" x 5.0"



### AR Series

10,000 – 50,000 lumen fixture



IP66 / IP67  
GN & HZ

16.4 kg | 36.0 lbs  
24.0" x 20.0" x 4.3"



### NL Series

3,970 – 14,313 lumen fixture



IP66  
GN & HZ

NL2: 5.3 kg | 12.0 lbs | 27.3" x 7.6" x 3.2"  
NL4: 8.6 kg | 19.0 lbs | 50.8" x 7.6" x 3.2"



### LS Series

1,550 lumens per module



IP66 / IP67  
HZ

Up to 30 LED modules per string  
1.2 kg | 2.6 lbs per module  
9.7" x 3.3" per module



### ZLM Series

22,000 – 28,000 lumen fixture



IP66  
GN

10.0 kg | 22.0 lbs  
15.5" x 6.8" x 7.1"



### EXC Series

1,220 lumen fixture



IP66  
HZ

4.4 kg | 9.8 lbs  
11.5" x 6.5" x 3.76"



## Product Catalog



## Quick Selection Guide

Application	Nemalux Model	NEC/CEC CLASS I				NEC/CEC CLASS II				UL1598	UL1598A	Lumen Output					Lens Material				Colour Temp.			Optical Profiles*						Environmental						
		Div. 1	Div. 2	Zone 1	Zone 2	Div. 1	Div. 2	Zone 20	Zone 21			Zone 22	500 - 5000	5000 - 10000	10000 - 20000	20000 - 30000	30000 - 50000	Polycarbonate	Glass	Clear	Frosted	3000 K	4000 K	5000 K	Wide Beam	Narrow Beam	Type 1	Type 2	Type 3	Type 4	Type 5	IP66	IP67	IP68**	Low Ambient	High Ambient
Pole Mount	AR Series		X		X		X			X	X	X	X	X					X	X	X	X	X	X	X	X	X	X	X	X	X	X	-40°C	+55°C		
	XR Series		X		X		X		X	X	X	X	X	X			X		X	X	X	X	X	X		X	X			X	X	X	-50°C	+75°C		
	MR Series		X		X		X			X	X	X	X	X					X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	-40°C	+55°C	
High Bay/ Low Bay	AR Series		X		X		X			X	X	X	X	X					X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	-40°C	+55°C	
	XR Series		X		X		X		X	X	X	X	X	X			X		X	X	X	X	X	X		X	X			X	X	X	-50°C	+75°C		
	MR Series		X		X		X			X	X	X	X	X					X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	-40°C	+55°C	
Yoke Mount	AR Series		X		X		X			X	X	X	X	X					X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	-40°C	+55°C	
	XR Series		X		X		X		X	X	X	X	X	X			X		X	X	X	X	X	X		X	X			X	X	X	-50°C	+75°C		
	MR Series		X		X		X			X	X	X	X	X					X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	-40°C	+55°C	
Linear	GS Series AC		X		X		X			X	X	X	X	X			X			X	X	X	X	X						X	X	X	-40°C	+65°C		
	GS Series DC		X		X		X			X	X	X	X	X			X			X	X	X	X	X						X	X	X	-40°C	+60°C		
	NL Series		X		X		X			X	X	X	X	X			X		X	X	X	X	X	X						X	X	X	-40°C	+53°C		
	BL Series		X		X		X		X	X	X	X	X	X			X	X	X	X	X	X	X	X						X	X	X	-50°C	+65°C		
Dark Sky Certified	AR Series		X		X		X			X	X	X	X	X					X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	-40°C	+55°C	
	XR Series		X		X		X		X	X	X	X	X	X			X		X	X	X	X	X	X		X	X			X	X	X	-50°C	+75°C		
	MR Series		X		X		X			X	X	X	X	X					X	X	X	X	X	X	X	X	X	X	X	X	X	X	-40°C	+55°C		
	GS Series AC		X		X		X			X	X	X	X	X			X			X	X	X	X	X						X	X	X	-40°C	+65°C		
	GS Series DC		X		X		X			X	X	X	X	X			X			X	X	X	X	X	X					X	X	X	-40°C	+60°C		
Specialty	EXC Series	X	X	X		X	X	X			X					X			X	X	X	X	X	X						X			-50°C	+58°C		
	CANLED Series		X														X		X	X	X	X	X							X			-40°C	+55°C		
	XCANLED Series		X														X		X	X	X	X	X	X						X			-40°C	+55°C		
Temporary	LS Series		X		X	X		X			X	X				X			X	X	X	X	X	X						X	X		-20°C	+60°C		
	ZLM Series										X			X		X		X		X	X	X	X	X	X	X				X			-40°C	+55°C		

Notes:

*\*Custom optics are available upon request*

**\*\*IP68 models are rated for General Location use only**