

MADE &
STOCKED IN
CALGARY,
ALBERTA

MR Series

MR6: 6,283 lumens | 10.4 lbs (4.6 kg)
Dimensions: 14.5" x 11.5" x 2.5"
Ambient temp. range: -40°C to +55°C

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



XR Series

XR20: 20,550 lumens | 17.8 lbs (8.1 kg)
Dimensions: 18.74" x 14.88" x 3.78"
Ambient temp. range: -50°C to +75°C

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



AR Series

AR30: 33,190 lumens | 36.0 lbs (16.4 kg)
Dimensions: 24.0" x 20.0" x 4.3"
Ambient temp. range: -40°C to +43°C

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



BL Series

BL40: 4,475 lumens | 6.4 lbs (2.9 kg)
Dimensions: 18.43" x 5.65" x 3.93"
Ambient temp. range: -50°C to +65°C

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



NL Series

NL2-S: 3,970 lumens | 12 lbs (5.3 kg)
Lengths: NL-2: 27.3"
Ambient temp. range: -40°C to +55°C

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



EXC Series

EXC: 1,220 lumens | 9.8 lbs (4.4 kg)
Dimensions: 11.5" x 6.5" x 3.76"
Ambient temp. range: -50°C to +58°C

Certifications
Class I, Division 1
Class II, Division 1
Class III, Division 1



GS Series

GS-1: 582 lumens | 1.8 lbs (0.8 kg)
GS-2: 1,292 lumens | 2.6 lbs (1.2 kg)
GS-3: 2,003 lumens | 3.9 lbs (1.8 kg)
GS-4: 2,714 lumens | 5.3 lbs (2.4 kg)
Lengths: GS-1: 15.5"; GS-2: 26.5";
GS-3: 37.5"; GS-4: 48.5"
Ambient temp. range: -40°C to +65°C

Certifications
Marine Rated
Class I, Division 2
Class II, Division 2
Class III



View All Products Online



MR6-50-WF-GY-HZ-AC

MR 6 SERIES; 5000K ; WIDE BEAM (NO OPTICS);
GREY FINISH; HAZARDOUS LOCATION; 120-277VAC

XR20-50-WC-GY-HZ-AC

XR 20 SERIES; 5000K ; WIDE BEAM (NO OPTICS);
GREY FINISH; HAZARDOUS LOCATION; 120-277VAC

AR30-50-WC-GY-HZ-AC

AR 30 SERIES; 5000K ; WIDE BEAM (NO OPTICS);
GREY FINISH; HAZARDOUS LOCATION; 120-277VAC

GS-1-50-W-BLK-H-120-66-A

GS SERIES; ONE FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS
LOCATION; 120 VAC 60Hz; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-1-50-W-BLK-O-120-66-A

GS SERIES; ONE FOOT; 5000K; WIDE BEAM; BLACK FINISH; ORDINARY
LOCATION; 120 VAC 60Hz; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-2-50-W-BLK-H-120-66-A

GS SERIES; TWO FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS
LOCATION; 120 VAC 60Hz; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-2-50-W-BLK-O-120-66-A

GS SERIES; TWO FOOT; 5000K; WIDE BEAM; BLACK FINISH; ORDINARY
LOCATION; 120 VAC 60Hz; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-3-50-W-BLK-H-120-66-A

GS SERIES; THREE FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS
LOCATION; 120 VAC 60Hz; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-3-50-W-BLK-O-120-66-A

GS SERIES; THREE FOOT; 5000K; WIDE BEAM; BLACK FINISH; ORDINARY
LOCATION; 120 VAC 60Hz; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-4-50-W-BLK-H-120-66-A

GS SERIES; FOUR FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS
LOCATION; 120 VAC 60Hz; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-4-50-W-BLK-O-120-66-A

GS SERIES; FOUR FOOT; 5000K; WIDE BEAM; BLACK FINISH; ORDINARY
LOCATION; 120 VAC 60Hz; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

EXC-50-WF-GY-HZ-AC

EXC SERIES; 5000K ; WIDE FROSTED; GREY FINISH; HAZARDOUS LOCATION;
120-277VAC

BL40-50-GY-HZ-AC

BL 40 SERIES; 5000K ; GREY FINISH;
HAZARDOUS LOCATION; 120-277VAC

NL2-S-50-WC-GY-HZ-AC

NL2 SERIES; STANDARD OUTPUT; 5000K ; WIDE CLEAR LENS;
GREY FINISH; HAZARDOUS LOCATION; 120-277VAC

GS-1-50-W-BLK-H-24-66-A

GS SERIES; ONE FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS
LOCATION; 24 VDC; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-1-50-W-BLK-O-24-66-A

GS SERIES; ONE FOOT; 5000K; WIDE BEAM; BLACK FINISH; ORDINARY
LOCATION; 24 VDC; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-2-50-W-BLK-H-24-66-A

GS SERIES; TWO FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS
LOCATION; 24 VDC; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-2-50-W-BLK-O-24-66-A

GS SERIES; TWO FOOT; 5000K; WIDE BEAM; BLACK FINISH; ORDINARY
LOCATION; 24 VDC; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-3-50-W-BLK-H-24-66-A

GS SERIES; THREE FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS
LOCATION; 24 VDC; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-3-50-W-BLK-O-24-66-A

GS SERIES; THREE FOOT; 5000K; WIDE BEAM; BLACK FINISH; ORDINARY
LOCATION; 24 VDC; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-4-50-W-BLK-H-24-66-A

GS SERIES; FOUR FOOT; 5000K; WIDE BEAM; BLACK FINISH; HAZARDOUS
LOCATION; 24 VDC; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

GS-4-50-W-BLK-O-24-66-A

GS SERIES; FOUR FOOT; 5000K; WIDE BEAM; BLACK FINISH; ORDINARY
LOCATION; 24 VDC; IP66 INGRESS PROTECTION; ADJUSTABLE MOUNT

EXC-50-WF-GY-HZ-DC

EXC SERIES; 5000K ; WIDE FROSTED; GREY FINISH; HAZARDOUS LOCATION;
22-28VDC